


45540 GLOBAL GB20H-3(12V18Ah)

Specifications


Nominal Voltage	12V	
Nominal Capacity (10HR)	18Ah	
Cold Cranking Performance Amps@0°F (-18°C)	300 CCA	
Dimension (±2mm)	Length	175mm
	Width	87mm
	Container Height	155mm
	Total Height	155mm
Battery (with acid)	Approx Weight	5.93kg
Terminal type	A	
Battery type	Factory Activated Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C ₁₀
	Voltage	14.40V~15.00V at 25°C
	Charging time	15~18h
	Constant-Current Charge:	
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage	13.50V~13.80V at 25°C
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%



General Features

- Maintenance-free
- Sealed and non-spillable AGM battery
- Shipped pre-charged and ready to install

Discharge Characteristics (25°C)



*Values are subject to variation of +/- 5% in normal manufacturing processes.